

NAME

CURLOPT_SSLCERT – set SSL client certificate

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_SSLCERT, char *cert);
```

DESCRIPTION

Pass a pointer to a zero terminated string as parameter. The string should be the file name of your client certificate. The default format is "P12" on Secure Transport and "PEM" on other engines, and can be changed with *CURLOPT_SSLCERTTYPE(3)*.

With NSS or Secure Transport, this can also be the nickname of the certificate you wish to authenticate with as it is named in the security database. If you want to use a file from the current directory, please precede it with "/" prefix, in order to avoid confusion with a nickname.

When using a client certificate, you most likely also need to provide a private key with *CURLOPT_SSLKEY(3)*.

DEFAULT

NULL

PROTOCOLS

All TLS based protocols: HTTPS, FTPS, IMAPS, POP3, SMTPS etc.

EXAMPLE

TODO

AVAILABILITY

If built TLS enabled.

RETURN VALUE

Returns *CURLE_OK* if TLS enabled, *CURLE_UNKNOWN_OPTION* if not, or *CURLE_OUT_OF_MEMORY* if there was insufficient heap space.

SEE ALSO

CURLOPT_SSLCERTTYPE(3), *CURLOPT_SSLKEY(3)*,